

免键轴衬
Keyless Bushings

高定心型

NEW
新产品
绿色字体型号

高定心型

CAD 2D 3D

型号 M 材质 S 表面处理 推荐安装尺寸

KBJC	45	S45C	-	轴:h8
KBJCB			四氧化三铁保护膜	轴:h9
KBJCN			无电解镀铬	

新型号

① 拆卸螺纹孔 锁紧螺栓

锁紧原理

① 拆卸用螺纹孔的螺纹径与锁紧螺栓相同。

① 相当于JB/T 79347 Z8标准

型式		尺寸(mm)						容许轴向 负载(KN)	容许最大 扭矩(N·m)	接触面压强(MPa)		锁紧螺栓								
型号	d	D	D ₁	L ₁	L ₂	L ₃	L			P _i	P _o	数量	规格	锁紧扭矩 (N·m)						
KBJC KBJCB KBJCN	19	47	56	17	22	28	34	26	243	234	94	5	M6×20	17						
	20								256	222										
	22								282	202										
	24	50	59					31	368	222	106	6								
	25								383	213										
	28	55	64						429	190	97									
	30	60	69					460	177	118	8									
	32							655	222											
	35							716	203											
	38	65	74					778	187	109										
	40							819	178											
	42	75	84	20	25	33	41	65	1361	227	127	7	M8×25	41						
	45								1458	212										
	50								1620	191					119					
	55	85	94					74	2037	199	129	8								
	60	90	99						2223	182	121									
	65	95	104						83	2710	189				129	9				
	70	110	119					24	30	40	50	120			4203	211	134	8	M10×30	83
	75	115	124												4754	197	128			
	80	120	129												4804	184	123			
	85	125	134									135			5742	195	133	9		
	90	130	139												6080	184	128			
	95	135	144	150	7131	194	137					10								
	100	145	154	175	8732	198						8								
	110	155	164		9605	180							128							
	120	165	174		196	11787	186						135	9	M12×35	145				

① 容许轴向推力是指扭矩为0时的数值。最大容许扭矩是轴向推力负载为0时的数值。为发挥免键轴衬的最佳性能，需要将轴、免键轴衬、轮毂等处的异物清除干净。

订货范例 Order 型式 KBJC19

5 个工作日

免键轴衬