



C形(扣环固定型)

型式			L	M		N	d		T	H	附属扣环	
型号	D公差选择	D	指定单位0.1mm	容差			容差				形状	JIS公称规格
KPVC KPVHC KPVNC KPVHNC KPVSC KPVCC	M (m6)	2	5.0 ~ 30.0	0.5	+ 0.050 0	2	1.5	+ 0.060 0	1.5	4.5	E型	No. 1.5
		3	5.0 ~ 50.0		2		0	5.5		No. 2		
		4			0.7		+ 0.100 0	3		+ 0.075 0		6.5
		5	4	8				No. 4				
		6	5	9				No. 5				
	P (p6)	8	10.0 ~ 100.0	0.9		7	+ 0.090 0	2	12	No. 7		
	H (h7)	10	15.0 ~ 100.0	1.15	+ 0.140 0	3	9.6	0 -0.090	2	14	C型	No.10
		12	15.0 ~ 200.0				11.5	0 -0.110		3		17
	F (f8)	13	25.0 ~ 200.0				12.4		18			No.13
		14					13.4		19			No.14
	C (c9)	15					30.0 ~ 200.0		14.3			20
		16	15.2						21			No.16
	LF(衬套用)	17	1.35						16.2			22
		18						17	23	No.18		
		20		19	0 -0.210	4		26	No.20			
		22		21				27	No.22			
		25		23.9				31	No.25			

B形(螺母固定型)

型式			L	H	B	T	F	(d)	(N)	M (粗牙)	附属螺母					
型号	D公差选择	D	指定单位0.1mm													
KPV B KPVH B KPVN B KPVH NB KPV SB KPV CB	M (m6)	4	5.0 ~ 50.0	7	5	3	6	3.9	1.5	M 3	M 3×0.5					
		5	5.0 ~ 60.0	9	7	4		4.9		M 4	M 4×0.7					
		6	10.0 ~ 100.0	10	8	5	9	5.8		M 5	M 5×0.8					
		8		13	10			7.8		M 6	M 6×1.0					
	P (p6)	10	15.0 ~ 200.0	16	13		12	9.8		M 8	M 8×1.25					
		12		18	14			16		11.8	M10	M10×1.5				
	H (h7)	13	25.0 ~ 200.0	24	21		18	12.8		M12	M12×1.75					
		14						13.8								
	F (f8)	15	30.0 ~ 200.0					14.8								
		16						15.8								
	C (c9)	17						16.8								
		18						17.8								
	LF(衬套用)	20	27	23			5	24		19.8	M16	M16×2.0				
		22								21.8						
		25						30		27			24.8			

M形(两端内螺纹型)

型式			L	M (粗牙)	N (粗牙)
型号	D公差选择	D	指定单位0.1mm		
KPV KPVH KPVNM KPVHNM KPVSM KPVCM	M (m6)	6	20.0 ~ 100.0	M 3	M 3
		8		M 5	M 5
		10	25.0 ~ 100.0	M 6	M 6
	P (p6)	12	25.0 ~ 200.0		
	H (h7)	13	35.0 ~ 200.0	M 8	M 8
		14			
	F (f8)	15	40.0 ~ 200.0	M 10	M 10
		16			
	C (c9)	17		M 12	M 12
		18			
	LF(衬套用)	20	50.0 ~ 200.0	M 16	M 16
		22			
		25			

S形(止动螺丝固定型)

型式			L	指定单位1mm		N				
型号	D公差选择	D	指定单位0.1mm	F	E					
KPV KPVH KPVNS KPVHNS KPVSS KPVCS	M (m6)	3	5.0 ~ 50.0	0≤F≤L/2	1≤E≤50	0.5				
		4								
		5	10.0 ~ 60.0			1				
		P (p6)	6				10.0 ~ 100.0			
	8									
	H (h7)	10	15.0 ~ 100.0				2			
		12	15.0 ~ 200.0							
		F (f8)	13			25.0 ~ 200.0				
			14							
	15									
	C (c9)	16	30.0 ~ 200.0							
		17								
		18								
	LF(衬套用)	20								
		22								
		25								

订货范例
Order

型式 - L - (LKA...)
KPVCM2 - 30 - NA3
KPVBM4 - 20 - LKA
KPVSM8 - 20 - MA3

订货范例
Order

型式 - L - F - E - (MMA...)
KPVHSM6 - 10 - F7 - E1 - MMA

5 个工作日

铰链销