

带座外球面轴承

Ball Bearing Units

铸铁制

圆形座嵌入型/滑块座型



BURCP



BURL



CAD 20 36

材质

①固定座	FC200
②轴承	SUJ2
③橡胶密封圈	丁腈橡胶(NBR)
④止动螺丝	SCM435

精度: JIS B 1558

JIS B 1514

JIS B 1559

使用温度: -15~+100℃





删除部分产品说明

①2-M(止动螺丝)的角度为120°。

②产品默认为过渡配合。

BURCP(圆形座嵌入型)

BURL(滑块座型)



型式		公称规格	W	P	P.C.D.	t	A	A ₁	A ₂	A ₃	E	d	B	S	基本额定负载(KN)		止动螺丝			重量 (g)	
型号	D														Cr(动)	Cor(静)	M	紧固扭矩 (N·m)	轴向负载 能力(KN)		
嵌入型 BURCP	12	UCFC201	100	55.1	78	7	28.3	20.5	10	5	62	12	31	12.7	12.8	6.6	M6×0.75	3.92	0.64	890	
	15	UCFC202																		870	
	17	UCFC203																		860	
	20	UCFC204																		840	
	25	UCFC205	115	63.6	90	7	29.8	21	10	6	70	12	34.1	14.3	14	7.9		4.9	1.4	970	
	30	UCFC206	125	70.7	100	8	32.2	23											8	80	14
	35	UCFC207	135	77.8	110	9	36.4	26	11	90	42.9	17.5	25.9	15.4	M8×1	11.8		2.59			
	40	UCFC208	145	84.8	120													10	100	49.2	19
	45	UCFC209	160	93.3	132	14	40.2	26	10	12	105	16	51.6	35.5			23.2				
	50	UCFC210	165	97.6	138													42.6	28	110	35.5

型式		公称规格	H	H ₁	H ₂	H ₃	L	L ₁	A	A ₁	A ₂	W ₁	W ₂	L ₂	d	B	S	基本额定负载(KN)		止动螺丝			重量 (g)							
型号	D																	Cr(动)	Cor(静)	M	紧固扭矩 (N·m)	轴向负载 能力(KN)								
滑块座型 BURL	12	UCT201	89	76	51	32	94	61	32	21	12	16	10	51	19	31	12.7	12.8	6.6	M6×0.75	3.92	0.64	790							
	15	UCT202																					770							
	17	UCT203																					760							
	20	UCT204																					740							
	25	UCT205	102	89	56	37	97	62	32	24	13	64	22	34.1	14.3	14	7.9	M8×1	11.8	1.28	740									
	30	UCT206					113	70	37	28				57	38.1	15.9	19.6			11.3	1.4	820								
	35	UCT207					129	78	37	30				64	42.9	17.5	25.9			15.4	1.96	1300								
	40	UCT208					114	144	88	33				83	49.2	19	29.3			17.9	M10×1.25	23.5	3.55	2500						
	45	UCT209					117	102	83	49				87	49	35	16			19					16	83	29	33	20.5	2400
	50	UCT210					149	90	37	16				19	16	86	51.6			35.5					23.2					

③ 三益不承诺轴承的品牌。



订货范例
Order

型式

- (HA)

BURCP12

BURCP12

- HA



3 个工作日

可选加工
型式

间隙配合

代码

HA

技术说明

带座外球面轴承轴承座与轴承为间隙配合时统一使用该可选加工