

固定环

Shaft Collars

固定轴承用开口型

短/长凸头型



型号		M 材质		S 表面处理	A 附件
短凸头型	长凸头型	国标	相当		(内六角螺栓)
FRNSB	FRNLB	45	S45C	四氧化三铁保护膜	1个(铜)
FRNSN	FRNLN			无电解镀锌	
FRNSS	FRNLS			—	
FRNSC	FRNLC	0Cr18Ni9	SUS304	本色阳极氧化处理	1个(不锈钢)
FRNSA	FRNLA	A2017	A2017	黑色阳极氧化处理	

其余²⁵✓

① D₃ ~ D₂₅: C0.5
D₃₀ ~ D₅₀: C1

短凸头型

长凸头型

型式	Ds	适用轴承(外径)	B	B ₁	D ₁	M (粗牙)	b	d	R	W	X	Y	Z
型号	D												
(短凸头型) FRNSB FRNSN FRNSS FRNSC FRNSA	3	5	9	12	16	M3	8	3.4	3	1	4.5	2.2	3~5
		6											
		8											
	4	7			18	M3	8	3.4	3	1	5	3	3.5~6
		9											
		7											
	5	8			20	M3	8	3.4	3	1	5.5	4	5~6.5
		10											
		8											
	6	9			22	M3	8	3.4	3	1	6	4	6~6.5
		12											
		11											
	8	12			25	M3	8	3.4	3	1	7	5	7~9
		14											
		13											
	10	13			30	M4	10	4.5	3.75	1.5	9	5	10
		14											
		16											
	12	14			34	M4	10	4.5	3.75	1.5	10	5	10
		15											
		16											
(长凸头型) FRNLB FRNLN FRNLS FRNLC FRNLA	15	17	14	17	20	M4	10	4.5	3.75	1.5	11.5	6	12
		18											
		19											
	17	20			22	M4	10	4.5	3.75	1.5	12	6	12
		21											
		22											
	20	23			25	M4	10	4.5	3.75	1.5	13	6	12
		24											
		27											
	25	28	14	17	20	M4	10	4.5	3.75	1.5	14	6	12
		29											
		30											
	30	31	17	21	25	M5	12	5.5	4.5	2	15	7	14
		32											
		33											
	35	34	21	25	30	M6	15	6.6	6	2	16	7	14
		35											
		36											
	40	37	21	25	35	M6	15	6.6	6	2	17	7	14
		38											
		39											
	50	40	26	32	40	M8	20	9	7	3	18	8	28
		41											
		42											

① 铝合金材质产品的 Ds 尺寸仅有带*符号的尺寸

订货范例
Order

-

型式
FRNSB3

-

Ds
5

7 个工作日