

等高螺栓

Shoulder Bolts

短头型 ·
短头自由指定型






短头型



CAD 2D 3D

型号	D公差	M 材质		H 硬度	强度分类
		国标	相当		
HSBL	e9	35CrMo	SCM435	28~37HRC	相当于9.8
HSBLS		0Cr18Ni9	SUS304	-	A2-50
HSBLG	g6	35CrMo	SCM435	28~37HRC	相当于9.8
HSBLGS		0Cr18Ni9	SUS304	-	A2-50
HSBLH	h7	35CrMo	SCM435	28~37HRC	相当于9.8
HSBLHS		0Cr18Ni9	SUS304	-	A2-50

其余 ✓



型式		L							
型号	D								
HSBL	4	*10	*15	*20					
	4.5	*10	*15	*20	25	30	35	40	
HSBLS	5	*10	*15	*20	*25				
HSBLG	5.5	*10	*15	*20	*25	30	35	40	
HSBLGS	6	*10	*15	*20	*25				
HSBLH	6.5	*10	*15	*20	*25	30	35	40	
HSBLHS	8	*10	*15	*20	*25	30	35	40	
	10	*10	*15	*20	*25	30	35	40	

◇ g6 · h7公差仅适用于带*符号的尺寸



订货范例
Order

型式 - L
HSBL4 - 10



5 个工作日

D公差				A	B	t	E	F	M x P	T
D	e9	g6	h7							
4				6.5			2	5	2.5 x 0.45	4.5
4.5				7	2.5	1.6	2	6	3 x 0.5	5
5	-0.02	-0.004	0	8			2	6		5.5
5.5	-0.05	-0.012	-0.012				2	6		6
6				9	3	2.2	2.5	6	4 x 0.7	6.5
6.5						2	2.5	7		
8	-0.025	-0.005	0	10	4	2.5	3	9	5 x 0.8	7
8	-0.061	-0.014	-0.015	13	5	3	4	9	6 x 1.0	8.7
10				16	6	4	5	12	8 x 1.25	10.8




短头自由指定型



CAD 2D 3D

型号	D公差	M 材质		H 硬度	强度分类
		国标	相当		
HSBLF	e9	35CrMo	SCM435	28~37HRC	相当于9.8
HSBLFS		0Cr18Ni9	SUS304	-	A2-50
HSBLFG	g6	35CrMo	SCM435	28~37HRC	相当于9.8
HSBLFGS		0Cr18Ni9	SUS304	-	A2-50
HSBLFH	h7	35CrMo	SCM435	28~37HRC	相当于9.8
HSBLFHS		0Cr18Ni9	SUS304	-	A2-50

其余 ✓



型式		L	F	L+F加工条件
型号	D	指定单位0.1mm	指定单位1mm	
HSBLF	4	10~40		L+F ≤ 45
	4.5	10~40		L+F ≤ 46
HSBLFS	5	10~40		L+F ≤ 46
HSBLFG	5.5	10~40		L+F ≤ 47
HSBLFGS	6	10~40		L+F ≤ 47
HSBLFH	6.5	10~50		L+F ≤ 59
HSBLFHS	8	10~60		L+F ≤ 70
	10	10~60		L+F ≤ 72

$M \leq F \leq M \times 3$

D公差				A	B	t	E	M x P	T
D	e9	g6	h7						
4				6.5			2	2.5 x 0.45	4.5
4.5				7	2.5	1.6	2	3 x 0.5	5
5	-0.02	-0.004	0	8			2		5.5
5.5	-0.05	-0.012	-0.012				2		6
6				9	3	2.2	2.5	4 x 0.7	6.5
6.5						2	2.5		
8	-0.025	-0.005	0	10	4	2.5	3	5 x 0.8	7
8	-0.061	-0.014	-0.015	13	5	3	4	6 x 1.0	8.7
10				16	6	4	5	8 x 1.25	10.8



订货范例
Order

型式 - L - F
HSBLF4 - 10 - 5



5 个工作日

等高螺栓