

铰孔螺栓

Reamer Bolts

标准型 · 全长指定型



标准型




CAD 2D 3D


型号		M 材质		S 表面处理
外六角标准型	内六角标准型	国标	相当	
RBR	RBH	45	S45C	四氧化三铁保护膜
RBRs	RBHs	0Cr18Ni9Cu3	SUSXM7	-

其余 $\sqrt{6.3}$

外六角标准型
RBR
RBRs(不锈钢)



内六角标准型
RBH
RBHs(不锈钢)



其余 $\sqrt{6.3}$

型式		L															
型号	Dg6																
RBR (D5~16)	5	-0.004	23 26 29			M 5	6	10	3	11.5	8.5	3.5	2.4	9	0.5		
	6	-0.012	23 26 29 32 35			M 6	8	4	4	10	4	3	3	9			
RBRs (D5~10)	8	-0.005	32 35 36 38			M 8	10	13	5	15	13	5	3.75	10.4	0.5		
RBH (D5~8)	10	-0.014	36 38 39 42			M10	12	17	19.6	6.5	6.5	4.5	3	12.9			
RBHs (D5~8)	12	-0.006	39 42 45 48 52 55			M12	16	19	-	21.9	-	8	-	15.4	1		
	16	-0.017	52 55 58			M16	20	22	25.4	10	10	6	-	19.4			



订货范例
Order

型式 - L
RBR5 - 23



7 个工作日

全长指定型




CAD 2D 3D


型号			M 材质		S 表面处理
外六角指定型	外六角无台指定型	内六角指定型	国标	相当	
RBRF	RBRFN	RBHF	45	S45C	四氧化三铁保护膜
RBRFS	RBRFNS	RBHFS	0Cr18Ni9Cu3	SUSXM7	-

其余 $\sqrt{6.3}$


外六角指定型
RBRF(D5~16)
RBRFS(D5~10)



外六角无台指定型
RBRFN(D5~10)
RBRFNS(D5~10)



内六角指定型
RBHF(D5~8)
RBHFS(D5~8)



其余 $\sqrt{6.3}$

型式			指定单位1mm		M	B	B ₁	(C)	A	H	t max.	t ₁ max.	d	a
型号	Dg6	L	F											
RBRF (D5~16)	5	-0.004	20~29	M≤F≤L- 5	M 5	10	3	11.5	8.5	3.5	2.7	2.4	9	0.5
RBRFS (D5~10)	6	-0.012	20~35		M 6		4		10	4	3	3		
RBRFN (D5~10)	8	-0.005	20~38	M≤F≤L-10 (RBHF RBHFS)	M 8	13	5	15	13	5	3.8	3.75	10.4	
RBRFNS (D5~10)	10	-0.014	20~42		M10	17	6	19.6	-	6.5	4.5	-	12.9	
RBHF (D5~ 8)	12	-0.006	20~55	RBHFS)	M12	19	8	21.9	-	8	5	-	15.4	1
RBHFS (D5~ 8)	16	-0.017	20~58		M16	22	10	25.4		10	6	-	19.4	



订货范例
Order

型式 - L - F
RBRF5 - 20 - F20



7 个工作日