

带座外球面轴承

Ball Bearing Units

铸铁制

菱形座标准型/简易型



BURD



BURDM



CAD 20 30



① 固定座	FC200
② 轴承	SUJ2
③ 橡胶密封圈	丁腈橡胶(NBR)
④ 止动螺丝	SCM435

②-M(止动螺丝)的角度为120°。
④产品默认为过渡配合。



精度:JIS B 1558
JIS B 1514
JIS B 1559
使用温度: -15~+100℃

删除部分产品说明

BURD(菱形座标准型)



BURDM(菱形座简易型)



型式		公称规格	L	L ₁	W	t	A	A ₁	A ₂	d	B	S	基本额定负载(KN)		止动螺丝			重量 (g)
型号	D												Cr(动)	Cor(静)	M	紧固扭矩 (N·m)	轴向负载 能力(KN)	
标准型 BURD	12	UCFL201	113	90	60	12	33.3	25.5	15	12	31	12.7	12.8	6.6	M6×0.75	3.92	0.64	470
	15	UCFL202																450
	17	UCFL203																440
	20	UCFL204																420
	25	UCFL205	130	99	68	14	35.8	27	16	16	34.1	14.3	14	7.9		M8×1	11.8	590
	30	UCFL206	148	117	80	14	40.2	31	18		38.1	15.9	19.6	11.3				900
	35	UCFL207	161	130	90	16	44.4	34	19		42.9	17.5	25.9	15.4	1200			
	40	UCFL208	175	144	100	16	51.2	36	21		49.2	19	29.3	17.9	2.93	1510		
	45	UCFL209	188	148	108	18	52.2	38	22	19			33	20.5	3.3	1900		
	50	UCFL210	197	157	115	18	54.6	40			51.6	35.5	23.2	M10×1.25	23.5	3.55	2200	

型式		L	L ₁	W	t	A	A ₁	A ₂	d	B	S	基本额定负载(KN)		止动螺丝			重量 (g)
型号	D											Cr(动)	Cor(静)	M	紧固扭矩 (N·m)	轴向负载 能力(KN)	
简易型 BURDM	12	81	63.5	56	9.5	25.5	18	9.5	7	22	6	9.55	4.8	M5×0.8	2.5	0.476	280
	15																270
	17																250
	20	90	71.5	63	11	28.7	20	11	10	24.7	7	12.8	6.6	M6×0.75	4.9	300	
	25	95	76	69		30.5	20			27	7.5	14	7.9			1.4	400
	30	113	90.5	79	12	34.3	22.5	12	12	30.3	8	19.6	11.3			1.96	580

④ 三益不承诺轴承的品牌。



订货范例
Order

型式

- (HA)

BURD12

BURD12

- HA



3 个工作日

可选加工 型式	间隙配合
代码	HA
技术说明	带座外球面轴承轴承座与轴承为间隙配合时统一使用该可选加工