

丝杠支撑座

Support Units

方型 · 狭小间距
固定侧

NEW

新型号

绿色字体型号

狭小间距型





CAD 3D

型号	主体材质	主体表面处理
BTW	S45C	四氧化三铁保护膜
BTWN		无电解镍
BTWB		低温镀黑铬

新型号

编号	名称	数量
1	轴承座	1
2	角接触球轴承5级	1对
3	压盖	1
4	间隔环	2
5	油封	2
6	固定螺母	1
7	防松小螺栓(附铜垫片)	1



丝杠支撑座

型式		轴承型号																								
型号	No.	D ₁	A	B	C	C ₁	C ₂	E	H ₁	h	H	L	L ₁	L ₂	L ₃	T	P	N	M	X	Y	Z				
BTW (四氧化三铁 保护膜)	10	10			34											16		15	M4	6.6	11	5	7000ATYDFC8P5			
	12	12	60	46	35	13	6	30	32.5	22	39	25	5	29	5	19	5.5	18				1.5	7001ATYDFC8P5			
	15	15	70	54	40	15		35	38	28	48	27	6	32	6	22						6.5	7002ATYDFC8P5			
	17	17	86	68	50		19	8	43	55	39	64		9	44	7	24	6.6				28	8.5	7203ATYDFC8P5		
BTWN (无电解镍)	20	20	88	70	52		8	44	50	34	60		35		8	43	8	30	22	M5	11	17.5	11	7004ATYDFC8P5		
BTWB (低温镀黑铬)	25	25	106	85	64	22	10	53	70	48	80	42	12	54		9	35	9	33				14	20	13	7205ATYDFC8P5
	30	30	128	102	76	23	11	64	78	51	89	45	14	61		40		11					14	20	13	7206ATYDFC8P5
	35	35	140	114	88	26	12	70	79	52	96	50	14	67	12				35							7207ATYDFC8P5
	40	40	160	130	100	33	14	80	90	60	110	61	18	76	15		50	14	37	M6	18	26	17.5	7208ATYDFC8P5		



订货范例

Order

型式

BTW10



5 个工作日

No.10时M变为4, No.35/No.40时M变为6




狭小间距带缓冲型



CAD 3D

型号	主体材质	主体表面处理
BTWU	S45C	四氧化三铁保护膜
BTWUN		无电解镍

编号	名称	数量
1	轴承座	1
2	角接触球轴承5级	1对
3	压盖	1
4	间隔环	2
5	油封	2
6	固定螺母	1
7	防松小螺栓(附铜垫片)	1
8	缓冲块	1



型式		D ₁	A	B	C	C ₁	C ₂	E	H ₁	h	H	L	L ₁	L ₂	L ₃	T	P	N	M	X	Y	Z	缓冲块尺寸				轴承型号		
型号	No.																						a	b	t	e			
BTWU (四氧化三铁 保护膜)	10	10	60	46	34	13	6	30	32.5	22	39	25	5	29	5	16		15	M4	6.6	11	5	35	12	10	5	7000ATYDFC8P5		
	12	12			35					25	43							19				5.5				1.5	6.5	6.5	7001ATYDFC8P5
	15	15	70	54	40	15		35	38	28	48	27	6	32	6	22		18				6.5				11.5	7002ATYDFC8P5		
BTWUN (无电解镍)	17	17	86	68	50	19	8	43	55	39	64	35	9	44	7	24		6.6	28	M5	9	14	8.5	44	16	15.5	7203ATYDFC8P5		
	20	20	88	70	52			44	50	34	60		8	43	8	30		22	16.5				7004ATYDFC8P5						
	25	25	106	85	64	22	10	53	70	48	80	42	12	54	9	35	9	33	11				17.5			11	67	18	14



订货范例

Order

型式

BTWU10



5 个工作日

No.10时M变为4