

旋转吊环螺栓

Screwable Lifting Points

拉环型 · 经济型



NEW
新产品
绿色字体型号



拉环型



CAD 2D 3D

型号	材质	表面处理
E-SLP	合金钢	静电喷涂

因烤漆工艺, 可能会导致产品吊装处部分区域未能烤漆。



特点:

- 可360° 旋转, 超230° 摆动。
- 内置滚珠结构, 受力均匀、旋转流畅。
- 受力方向改变时, 吊环随力的方向旋转, 吊环不会产生扭矩。
- 不同受力方向, 可吊起载荷不同, 但保证4倍安全系数。
- 安装便捷。吊环底座外六方的设计可将吊点轻松安装在被吊物体上。
- 螺纹规格齐全, 额定载荷范围广。

适合受力范围: 230°







可360° 旋转

型式		螺纹MxP	D	B	A	D ₁	D ₂	L	H	F	净重(kg)
型号	No.										
E-SLP	8	M 8x1.25	12	44	30	40	37	12	46	98	0.44
	10	M10x1.5	12	44	30	40	37	19	46	98	0.45
	12	M12x1.75	12	44	30	40	37	19	46	98	0.45
	16	M16x2.0	12	44	30	40	37	31.8	46	98	0.48
	16B	M16x2.0	16	56.5	34	59	54.5	30	64.5	134.5	1.35
	20	M20x2.5	16	56.5	34	59	54.5	30	64.5	134.5	1.4
	20B	M20x2.5	20	67	40	70	64.3	38.1	76	160	2.3
	24	M24x3.0	16	56.5	34	59	54.5	30	64.5	134.5	1.4
	24B	M24x3.0	20	67	40	70	64.3	38.1	76	160	2.35
	30	M30x3.5	22	95	51	79	74	50	91	206	3.75
	36	M36x4.0	22	95	51	79	74	54	91	206	3.9
	42	M42x4.5	26	108	65	93	85	63	100.5	230.5	5.9
	48	M48x5.0	26	108	65	93	85	68	100.5	230.5	6.15
	52	M52x5.0	32	120	70	105	95	84	132	278	10
	56	M56x5.5	32	120	70	105	95	84	132	278	10
	64	M64x6.0	32	120	70	105	95	95	132	278	10.7

①设计安全系数为4:1。

工作极限载荷

吊环安装方式												
			1	2	1	2	2	2	2	3~4	3~4	3~4
吊环数量			1	2	1	2	2	2	2	3~4	3~4	3~4
起吊角度			0°	0°	90°	90°	0~45°	45~60°	不对称	0~45°	45~60°	不对称
形式		螺纹MxP	工作极限载荷(吨)									
型号	No.											
E-SLP	8	M 8x1.25	0.6	1.2	0.4	0.8	0.4	0.3	0.3	0.6	0.4	0.3
	10	M10x1.5	0.9	1.8	0.6	1.2	0.6	0.4	0.4	0.9	0.6	0.4
	12	M12x1.75	1.2	2.4	0.7	1.5	0.8	0.6	0.6	1.2	0.9	0.6
	16	M16x2.0	2.6	5.2	1.5	3	1.8	1.3	1.3	2.7	1.9	1.3
	16B	M16x2.0	3	6	1.9	3.8	2	1.5	1.5	3	2.1	1.5
	20	M20x2.5	3.5	7	2	4	2.4	1.7	1.7	3.5	2.5	1.7
	20B	M20x2.5	4	8	2.5	5	2.8	2	2	4.2	3	2
	24	M24x3.0	5	10	3.15	6.3	3.4	2.5	2.5	5.2	3.6	2.5
	24B	M24x3.0	7	14	4	8	4.9	3.5	3.5	7.3	5.2	3.5
	30	M30x3.5	10	20	6	12	7	5	5	10.5	7.5	5
	36	M36x4.0	15	30	10	20	14	10	10	21	15	10
	42	M42x4.5	17	34	13	26	18.2	13	13	27.3	19.5	13
	48	M48x5.0	18	36	14	28	19.6	14	14	29.4	21	14
	52	M52x5.0	25	50	20	40	28	20	20	42	30	20
	56	M56x5.5	28	56	20	40	28	20	20	42	30	20
	64	M64x6.0	28	56	20	40	28	20	20	42	30	20



订货范围
Order

型式
E-SLP10



3 个工作日

旋转吊环螺栓