

导向轴

Precision Linear Shafts

经济型·直杆型



NEW

新产品

绿色字体型号





型号	材质	硬度	表面处理
E-GSABY	45 (相当于S45C)	55HRC~ 高频淬火	镀硬铬 镀层硬度HV750~ 镀层厚度3μ以上

① 轴端加工部分可能会因加工的退火效应而导致硬度降低。
② 轴两端面及加工部无镀层。
③ 非标规格可来图定制。



型号	型式		L 指定单位1mm	C
	Dg7	公差		
E-GSABY	3	-0.002 -0.012	10 ~ 400	0.2以下
	4	-0.004	10 ~ 400	
	5	-0.016	10 ~ 400	
	6	-0.016	20 ~ 800	
	8	-0.005	20 ~ 1000	0.5以下
	10	-0.020	20 ~ 1000	
	12	-0.006	20 ~ 1200	
	13	-0.017	25 ~ 1200	
	15	-0.017	30 ~ 1200	
	16	-0.017	30 ~ 1200	
	20	-0.007	30 ~ 1200	1.0以下
	25	-0.028	35 ~ 1200	
	30	-0.028	35 ~ 1500	
	35	-0.028	35 ~ 1500	
	40	-0.009	50 ~ 1500	
	50	-0.034	65 ~ 1500	

可选加工形式	变更L尺寸公差	可选扳手槽加工	可选平面加工	2处可选平面加工																																																			
																																																							
代码	LKA	SA	FA	WFA																																																			
技术说明	变更L尺寸公差 书写方式LKA L<200时变更为L±0.03 200≤L<500时变更为L±0.05 500≤L 变更为L±0.1 使用LKA时, L尺寸指定单位可为0.1mm	可选扳手槽加工 书写方式SA2 D=6以上适用。 SA=指定单位1mm SA+e≤L SA≥0 <table><tr><th>D</th><th>W</th><th>e</th></tr><tr><td>6</td><td>5</td><td rowspan="3">8</td></tr><tr><td>8</td><td>7</td></tr><tr><td>10</td><td>8</td></tr><tr><td>12</td><td>10</td><td rowspan="3">10</td></tr><tr><td>13</td><td>11</td></tr><tr><td>16</td><td>14</td></tr><tr><td>20</td><td>17</td><td></td></tr><tr><td>25</td><td>22</td><td></td></tr><tr><td>30</td><td>27</td><td>15</td></tr><tr><td>35</td><td>30</td><td>15</td></tr><tr><td>40</td><td>36</td><td>20</td></tr><tr><td>50</td><td>41</td><td>20</td></tr></table>	D	W	e	6	5	8	8	7	10	8	12	10	10	13	11	16	14	20	17		25	22		30	27	15	35	30	15	40	36	20	50	41	20	可选平面加工 书写方式FA10-A8 D=6以上适用。 FA、A=指定单位 1mm FA≤3×D 1.5×D<FA时, FA≤L/2 A=0或A≥2 ⊗不可与WFA同时选用。 <table><tr><th>D</th><th>h</th></tr><tr><td>6~16</td><td>1</td></tr><tr><td>20~40</td><td>2</td></tr><tr><td>50</td><td>3</td></tr></table>	D	h	6~16	1	20~40	2	50	3	2处可选平面加工 书写方式WFA10-A8-E20 D=6以上适用。 WFA、A、E=指定单位1mm WFA≤3×D 1.5×D<WFA时, 2WFA≤L/2 A(E)=0或A(E)≥2 ⊗加工的两平面不能在同一平面上, 不可与FA同时选用 <table><tr><th>D</th><th>h</th></tr><tr><td>6~16</td><td>1</td></tr><tr><td>20~40</td><td>2</td></tr><tr><td>50</td><td>3</td></tr></table>	D	h	6~16	1	20~40	2	50	3
	D	W	e																																																				
6	5	8																																																					
8	7																																																						
10	8																																																						
12	10	10																																																					
13	11																																																						
16	14																																																						
20	17																																																						
25	22																																																						
30	27	15																																																					
35	30	15																																																					
40	36	20																																																					
50	41	20																																																					
D	h																																																						
6~16	1																																																						
20~40	2																																																						
50	3																																																						
D	h																																																						
6~16	1																																																						
20~40	2																																																						
50	3																																																						

订货范例 Order 型式 E-GSABY6 - L 20

5 个工作日

安装范例

对于导向轴的固定方法, 可通过开口加工型等进行固定。

