

固定中型

型式			安装螺纹 M×P	行程 S mm	最大 吸收 能量 Nm	小时 吸收 能量 Nm	最大 有效 重量 kg	最高 撞击 速度 m/s	基本尺寸							
型号	No.	速度							L	L ₁	C	d ₁	E	d	H	T
SACM (带受撞头) SACMN (无受撞头)	1412	H	M14×1.5	12	20	36000	8	4	99	76	70	4	11	12	19	6
		M					50	2								
		L					100	1								
	1416	H	M14×1.5	16	22	38000	10	4	122	95	89					
		M					90	2								
		L					180	1								
	1416C	H	M14×1.5	16	22	30000	10	4	103	76	70					
		M					90	2								
		L					180	1								
	1425	H	M14×1.5	25	30	38000	45	4	131	95	89					
		M					160	2								
		L					250	1								
	1612	H	M16×1.5	12	20	38000	8	4	99	76	70			13.8		
		M					50	2								
		L					100	1								
	2016	H	M20×1.5	16	35	42000	60	4	120.1	88.6	81.6					
		M					250	2								
		L					600	1								
	2020	H	M20×1.5	20	45	45000	90	4	145	109.5	102.5					
		M					300	2								
		L					700	1								
	2030	H	M20×1.5	30	59	45000	90	4	155	109.5	102.5					
		M					300	2								
		L					700	1								
	2040	H	M20×1.5	40	68	65000	100	4	188	132.5	125.5					
		M					300	2								
		L					1000	1								
	2050	H	M20×1.5	50	75	72000	100	4	229	163.5	156.5					
		M					400	2								
		L					1200	1								
	2525	H	M25×1.5	25	89	57000	200	4	154.5	111	104	8	18.5	22	32	10
		M					800	2								
		L					1300	1								
	2530	H	M25×1.5	30	98	60000	200	4								
		M					800	2								
		L					1300	1								
	2725	H	M27×1.5	25	130	75000	400	4	154.5							
		M					1000	2								
		L					2200	1								

固定大型

型式			安装螺纹 M×P	行程 S mm	最大吸收 能量 Nm	小时 吸收 能量 Nm	最大 有效 重量 kg	最高 撞击 速度 m/s	基本尺寸																							
型号	No.	速度							L	L ₁	C	d ₁	E	d	G	H	T															
SACB (带受撞头)	2540	H	M25×1.5	40	115	75000	300	4	213.8	137	120	8	36.8	22	10	32	10															
		M					900	2																								
		L					1400	1																								
	2550*	H	M25×1.5	50	135	90000	200	4	230.5	162	155							18.5	-	41												
		M					1100	2																								
		L					1600	1																								
	2580*	H	M25×1.5	80	160	100000	300	4	298.5	200	193		18.5		-						41											
		M					1200	2																								
		L					1800	1																								
	2750*	H	M27×1.5	50	250	95000	800	4	239	170.5	100							18.5	-			41										
		M					1900	2																								
		L					3500	1																								
SACBN (无受撞头)	3325	H	M33×1.5	25	180	100000	720	4	153.5	107	89		10	22	29								10	46	12							
		M					2000	2																								
		L					2880	1																								
	3350	H	M33×1.5	50	300	120000	1200	4	222	150	126							22	35.5							17	46	12				
		M					3300	2																								
		L					4800	1																								
	3625	H	M36×1.5	25	220	135000	880	4	159.5	107	89			22	35.5								17						46	12		
		M					2400	2																								
		L					3500	1																								
	3650	H	M36×1.5	50	350	150000	1400	4	228	150	126							22	35.5							17					46	12
		M					2500	2																								
		L					5600	1																								
3660	H	M36×1.5	60	360	150000	1400	4	238	150	126	22	35.5		17	46	12																
	M					2500	2																									
	L					5600	1																									