

Support Units

方型
固定側



标准带缓冲型















CAD 2D 3D

型号	M 主体材质	S 主体表面处理
BT KU	S45C	四氧化三铁保护膜
BT KUN		无电解镀镍

编号	名称	数量
1	轴承座	1
2	角接触球轴承5级	1对
3	压盖	1
4	间隔环	2
5	油封	2*
6	固定螺母	1
7	防松小螺栓(附铜垫片)	1
8	缓冲块	1

❗ *No.6・8仅有一个油封。



型式		D ₁	A	B	C	E	H ₁	h	H	L	L ₁	L ₂	L ₃	M	X	Y	Z	T	W	C ₁	C ₂	缓冲块尺寸				轴承型号	
型号	No.																					a	b	t	e		
BTKU (四氧化三铁 保护膜) BTKUN (无电解镀锌)	6	6	42	30	18	21	20	13	25	20	5.5	22	3.5	M3	5.5	9.5	11	12	1.5			30	11	10	1.5	706 ATYDFC7P5	
	8	8	52	38	25	26	26	17	32	23	7	26	4		6.6	11	12	14								4.5	7000ATYDFC8P5
	10	10	70	52	36	35	24	25	43	24	6	29.5	6	9			16								6.5	7001ATYDFC8P5	
	12	12															19			0.5			35		12		
	15	15	80	60	41	40	25	30	49	25		36	5	M4				22	5.0			44	16			7002ATYDFC8P5	
	20S	20	95	75	56	47.5	45	30	58	42	10	50	10		11	17	15	30		22	10					11	7204ATYDFC7P5
	20						25	35	68	48	13	60	14						35	1.0			67	18			7204ATYDFC7P5
25	25	105	85	66	52.5									M5											13.5	7205ATYDFC7P5	



🔥 订货范例
Order

型式

BTKU6



5 个工作日

No.10时M变为4