

# 固定环

## Shaft Collars

经济型  
开口型 · 分离型



NEW  
新产品  
绿色字体型号

### 开口型



CAD 2D 3D



①  $+0.05$   
 $D_{+0.01}$  为开槽加工前的公差。

① D6~D25: C0.5  
D30: C1

| 型号      | 材质  | 表面处理     | 附件         |
|---------|-----|----------|------------|
| E-FRBBC | 铝合金 | 本色阳极氧化处理 | 1个内六角螺栓(钢) |



其余  $\sqrt{25}$

| 型式      |    | B<br>选择 | D <sub>1</sub> | M<br>(粗牙螺纹) | d   | H   | (W) | X    | Y  |
|---------|----|---------|----------------|-------------|-----|-----|-----|------|----|
| 型号      | D  |         |                |             |     |     |     |      |    |
| E-FRBBC | 6  | 8       | 20             | M3          | 3.4 | 6   | 1   | 6    | 4  |
|         |    | 10      | 20             | M4          | 4.5 | 7.5 | 1   | 6    | 4  |
|         | 8  | 8       | 25             | M3          | 3.4 | 6   | 1.5 | 8    | 5  |
|         |    | 10      | 25             | M4          | 4.5 | 7.5 | 1.5 | 8    | 5  |
|         | 10 | 8       | 30             | M3          | 3.4 | 6   | 1.5 | 9    | 5  |
|         |    | 10      | 30             | M4          | 4.5 | 7.5 | 1.5 | 9    | 5  |
|         | 12 | 8       | 30             | M3          | 3.4 | 6   | 1.5 | 10   | 5  |
|         |    | 10      | 30             | M4          | 4.5 | 7.5 | 1.5 | 10   | 5  |
|         | 15 | 10      | 34             | M4          | 4.5 | 7.5 | 1.5 | 11.5 | 6  |
|         |    | 12      | 35             | M5          | 5.5 | 9   | 1.5 | 12   | 6  |
|         | 16 | 10      | 35             | M5          | 5.5 | 9   | 1.5 | 12   | 6  |
|         |    | 12      | 35             | M5          | 5.5 | 9   | 1.5 | 12   | 6  |
|         | 20 | 12      | 40             | M5          | 5.5 | 9   | 1.5 | 14   | 7  |
|         |    | 15      | 45             | M6          | 6.6 | 12  | 1.5 | 15   | 8  |
|         | 25 | 12      | 45             | M5          | 5.5 | 9   | 1.5 | 17   | 7  |
|         |    | 15      | 50             | M6          | 6.6 | 12  | 1.5 | 18   | 10 |
|         | 30 | 15      | 55             | M6          | 6.6 | 12  | 1.5 | 20   | 10 |



订货范例  
Order

型式 - B  
E-FRBBC6 - 8



5 个工作日

### 分离型



CAD 2D 3D



①  $+0.05$   
 $D_{+0.01}$  为开槽加工前的公差。

① D6~D25: C0.5  
D30: C1

| 型号      | 材质  | 表面处理     | 附件         |
|---------|-----|----------|------------|
| E-FRCBC | 铝合金 | 本色阳极氧化处理 | 2个内六角螺栓(钢) |



其余  $\sqrt{25}$

| 型式      |    | B<br>选择 | D <sub>1</sub> | M<br>(粗牙螺纹) | d   | H   | (W) | X    | Y  |
|---------|----|---------|----------------|-------------|-----|-----|-----|------|----|
| 型号      | D  |         |                |             |     |     |     |      |    |
| E-FRCBC | 6  | 8       | 20             | M3          | 3.4 | 6   | 1   | 6    | 4  |
|         | 8  | 8       | 25             | M3          | 3.4 | 6   | 1.5 | 8    | 5  |
|         |    | 10      | 25             | M4          | 4.5 | 7.5 | 1.5 | 8    | 5  |
|         | 10 | 8       | 30             | M3          | 3.4 | 6   | 1.5 | 9    | 5  |
|         |    | 10      | 30             | M4          | 4.5 | 7.5 | 1.5 | 9    | 5  |
|         | 12 | 8       | 30             | M3          | 3.4 | 6   | 1.5 | 10   | 5  |
|         |    | 10      | 30             | M4          | 4.5 | 7.5 | 1.5 | 10   | 5  |
|         | 15 | 10      | 34             | M4          | 4.5 | 7.5 | 1.5 | 11.5 | 6  |
|         |    | 12      | 35             | M5          | 5.5 | 9   | 1.5 | 12   | 6  |
|         | 16 | 10      | 35             | M5          | 5.5 | 9   | 1.5 | 12   | 6  |
|         |    | 12      | 35             | M5          | 5.5 | 9   | 1.5 | 12   | 6  |
|         | 20 | 12      | 40             | M5          | 5.5 | 9   | 1.5 | 14   | 7  |
|         |    | 15      | 45             | M6          | 6.6 | 12  | 1.5 | 15   | 8  |
|         | 25 | 12      | 45             | M5          | 5.5 | 9   | 1.5 | 17   | 7  |
|         |    | 15      | 50             | M6          | 6.6 | 12  | 1.5 | 18   | 10 |
|         | 30 | 15      | 55             | M6          | 6.6 | 12  | 1.5 | 20   | 10 |



订货范例  
Order

型式 - B  
E-FRCBC6 - 8



5 个工作日