

无油衬套

Oil Free Bushings

经济型 · 内径F7外径h7
圆/方/两面切割法兰型




NEW
新产品
绿色字体型号




材质: 高力黄铜+石墨


去掉部分备注



A部详图




圆法兰型
E-RDTZ
d=6~13




2-安装孔

d=16~50




4-安装孔

方法兰型
E-RDTSZ
d=6~13




4-安装孔

d=16~50




4-安装孔

两面切割法兰型
E-RDTNZ
d=6~13



2-安装孔

d=16~50



4-安装孔

① 内径F7型推荐配套轴 d8:一般用(重载) e7:一般用(轻载)
f8:高精度用 g6:高精度用(间歇负载)

② 使用注意事项 推荐用止转螺丝固定衬套。 ③ 特长: 法兰一体型规格, 可减少组装工时。

型式		L选择	D _{h7}		H	T	t	d ₁	d ₂	P.C.D.	W	F	A	短头内六角螺栓
型号	d _{F7}													
圆法兰型 E-RDTZ	6	+0.022 +0.010	10 15 20 25	10	0 -0.015	25	4	2.2	3.5	6	17	20	17	M3-10×2(4)
	8	+0.028 +0.013	15 20 25 30	12	0 -0.018	27	4	2.2	3.5	6	19	22	19	
	10		15 20 25 30	14		29	4	2.2	3.5	6	21	23	21	
	12		15 20 25 30 35	18	0 -0.021	36	5	3	4.5	7.5	26	28	26	M4-12×2(4)
	13	+0.034 +0.016	20 25 30 35 40	19		37	5	3	4.5	7.5	27	29	27	
方法兰型 E-RDTSZ	16		20 25 30 35 40 50	22		40	5	3	4.5	7.5	30	31	24	M4-12×4
两面切割 法兰型 E-RDTNZ	20		20 25 30 35 40 50 60	28	0 -0.025	49	6	3.7	5.5	9	38	38	22	M5-16×4
	25	+0.041 +0.020	25 30 35 40 50 60 70	33		54	6	3.7	5.5	9	43	42	25	
	30		30 35 40 50 60 70	38		63	8	4.2	6.6	11	50	50	30	M6-20×4
	35		35 40 50 60 70 80	44	0 -0.030	69	8	4.2	6.6	11	56	54	36	
	40	+0.050 +0.025	40 50 60 70 80 100	50		82	10	5.2	9	14	66	64	38	M8-25×4
	50		50 60 70 80 100	62		94	10	5.2	9	14	78	73	50	

- ① () 内附件数量为方法兰型E-RDTSZ。
 ② 新产品规格持续增加中, 如无所需规格请联系三益。
 ③ 不同于标准品, 经济型的安装螺栓需要另外购买。



订货范例 Order

型式

-

L

E-RDTZ6 - 15



5 个工作日

无油衬套