

同步带轮

Timing Pulleys

P2M型
K·B形




CAD 3D

型式	M 材质		S 表面处理	A 附件 固定螺丝
皮带宽度6mm	带轮	法兰		
A:7.5 W:11.5 L:20				
TPAC□□P2M060	铝合金	铝合金	本色阳极氧化处理	不锈钢


① 轴孔规格H(圆孔)·V(台阶孔)时,无螺纹孔。另外,有的尺寸可能带有螺纹孔避让。
② 小部分加工部位可能无表面处理。

■选择带轮形状

K形



B形




■选择轴孔规格


H圆孔




P圆孔+螺纹孔



N键槽孔+螺纹孔



V台阶孔



型式			带轮 形状	轴孔规格(指定单位1mm)							P.D.	O.D.	D	F	E
型号	齿数	种类 公称宽度		H	P	N(C)		V							
				d				V	Z	J					
(铝合金) TPAC	14	P2M060 A: 7.5 W: 11.5 L: 20	K	-	3 · 4	-	-	-	8.91	8.4	12	12	6		
	15				3 · 4 · 5				9.55	9.04	13				
	16				3 · 4 · 5				10.19	9.68		14	8		
	18				3-6				11.46	10.95	15				
	20				4-6.35				12.73	12.22	17	16	10		
	22				4-6.35				14.01	13.5					
	24				4-6.35				15.28	14.77					
	25				4-6.35				15.92	15.41				20	
	28		B	5-8	5-6.35	5-6	7-8	17.83	17.32	12	25	16			
	30			5-8	5-8	5-6	7-8	19.1	18.59						
	32			5-8	5-8	5-6	7-8	20.37	19.86				28	18	
	36			5-10	5-8	5-8	7-10	22.92	22.41						14
	40			5-12	5-10	8	5-10	7-12	25.46	24.96	16	32	23		
	42			5-14	5-12	8 · 10 · NK10	5-12	7-14	26.74	26.23					
	44			5-14	5-12	8 · 10 · NK10	5-12	7-14	28.01	27.5	18			35	25
	48			5-14	5-12	8 · 10 · NK10	5-12	7-14	30.56	30.05					
	50		5-18	5-15	8 · 10 · NK10-11-13	5-14	7-16	31.83	31.32	22	40	28			
	60		5-24	5-19	8 · 10 · NK10-11-18	5-17	7-19	38.2	37.69	28	44	32			