


同步带 Timing Belts

经济型 · 高扭矩型
S□M



- ① 使用温度 橡胶: -30~90℃
- ② 皮带周长为芯线长度。
- ③ 三益不承诺此产品品牌。
- ④ 产品背面型号为供应型号。

CAD 100 100

材料编号		M 材质						
橡胶 (-R)		① 背面橡胶		氯丁橡胶				
		② 齿橡胶		氯丁橡胶				
		③ 芯线		玻璃纤维				
		④ 底布		尼龙帆布				
种类	齿距	R	Lr	H	h	i	PLD	单位重量g/m (宽度: 10mm)
S2M	2	1.3	1.3	1.36	0.76	0.6	0.254	13
S3M	3	1.95	1.95	1.94	1.14	0.8	0.381	19
S5M	5	3.25	3.25	3.41	1.91	1.5	0.48	34
S8M	8	5.2	5.2	5.3	3.05	2.25	0.686	52
S14M	14	9.1	9.1	10.2	5.3	4.9	1.397	100

■种类 S2M(齿距: 2mm)			橡胶(-R)	
型式			齿数	皮带周长 (mm)
型号	皮带编号	皮带宽度mm (公称宽度)		
E-	120 S2M	4 (040)	60	120
	172 S2M		86	172
	186 S2M		93	186
	190 S2M		95	190
	200 S2M		100	200
	210 S2M		105	210
	212 S2M	6 (060)	106	212
	240 S2M		120	240
	260 S2M		130	260
	286 S2M		143	286
	288 S2M		144	288
	320 S2M	10 (100)	160	320
	356 S2M		178	356
	360 S2M		180	360
	366 S2M		183	366
	400 S2M		200	400
	426 S2M		213	426
	438 S2M		219	438
	452 S2M		226	452
	478 S2M	15 (150)	239	478
	522 S2M		261	522
	648 S2M		324	648
	3000 S2M		1500	3000

■种类 S3M(齿距: 3mm)			橡胶(-R)	
型式			齿数	皮带周长 (mm)
型号	皮带编号	皮带宽度mm (公称宽度)		
E-	285 S3M	6 (060)	95	285
	288 S3M		96	288
	294 S3M		98	294
	297 S3M		99	297
	300 S3M		100	300
	309 S3M		103	309
	312 S3M	10 (100)	104	312
	321 S3M		107	321
	324 S3M		108	324
	327 S3M		109	327
	330 S3M		110	330
	333 S3M	15 (150)	111	333
	339 S3M		113	339
	354 S3M		118	354
	357 S3M		119	357
	360 S3M		120	360
	363 S3M		121	363
	366 S3M	20 (200)	122	366
	369 S3M		123	369
	384 S3M		128	384
	390 S3M		130	390
	396 S3M		132	396
	399 S3M		133	399
	402 S3M	25 (250)	134	402
	405 S3M		135	405
	408 S3M		136	408
	420 S3M		140	420
	432 S3M		144	432
	435 S3M		145	435
	447 S3M	30 (300)	149	447
	450 S3M		150	450
	453 S3M		151	453
	465 S3M		155	465
	480 S3M		160	480
	486 S3M	35 (350)	162	486
	498 S3M		166	498
	501 S3M		167	501
	504 S3M		168	504
	510 S3M		170	510
	513 S3M	40 (400)	171	513
	519 S3M		173	519
	537 S3M		179	537
	540 S3M		180	540
	549 S3M		183	549
	555 S3M	45 (450)	185	555
	564 S3M		188	564
	567 S3M		189	567
	570 S3M		190	570
	582 S3M		194	582
	621 S3M	50 (500)	207	621
	633 S3M		211	633
	660 S3M		220	660
	666 S3M		222	666
	714 S3M		238	714
	720 S3M	55 (550)	240	720
	741 S3M		247	741
	753 S3M		251	753
	960 S3M		320	960
	1119 S3M		373	1119
	3210 S3M		1070	3210

■种类 S5M(齿距: 5mm)			橡胶(-R)	
型式			齿数	皮带周长 (mm)
型号	皮带编号	皮带宽度mm (公称宽度)		
E-	225 S5M	10 (100)	45	225
	250 S5M		50	250
	255 S5M		51	255
	260 S5M		52	260
	270 S5M		54	270
	275 S5M	15 (150)	55	275
	285 S5M		57	285
	295 S5M		59	295
	300 S5M		60	300
	320 S5M		64	320
	325 S5M	20 (200)	65	325
	330 S5M		66	330
	340 S5M		68	340
	350 S5M		70	350
	355 S5M		71	355
	375 S5M		75	375
	390 S5M	25 (250)	78	390
	400 S5M		80	400
	410 S5M		82	410
	415 S5M		83	415
	420 S5M		84	420
	425 S5M	30 (300)	85	425
	435 S5M		87	435
	450 S5M		90	450
	465 S5M		93	465
	475 S5M		95	475
	480 S5M		96	480
	490 S5M	35 (350)	98	490
	500 S5M		100	500
	510 S5M		102	510
	520 S5M		104	520
	525 S5M		105	525
	530 S5M	40 (400)	106	530
	550 S5M		110	550
	560 S5M		112	560
	565 S5M		113	565
	570 S5M		114	570
	575 S5M	45 (450)	115	575
	600 S5M		120	600
	615 S5M		123	615
	625 S5M		125	625
	635 S5M		127	635
	650 S5M	50 (500)	130	650
	665 S5M		133	665
	670 S5M		134	670
	675 S5M		135	675
	680 S5M		136	680
	690 S5M	55 (550)	138	690
	695 S5M		139	695
	700 S5M		140	700
	710 S5M		142	710
	725 S5M		145	725
	730 S5M	60 (600)	146	730
	740 S5M		148	740
	750 S5M		150	750
	780 S5M		156	780
	800 S5M		160	800
	810 S5M	65 (650)	162	810
	830 S5M		166	830
	835 S5M		167	835
	850 S5M		170	850

■种类 S3M(齿距: 3mm)			橡胶(-R)	
型式			齿数	皮带周长 (mm)
型号	皮带编号	皮带宽度mm (公称宽度)		
E-1752S3M 下架	135 S3M	6 (060)	45	135
	141 S3M		47	141
	171 S3M		57	171
	174 S3M		58	174
	177 S3M		59	177
	180 S3M		60	180
	189 S3M	10 (100)	63	189
	192 S3M		64	192
	195 S3M		65	195
	201 S3M		67	201
	204 S3M		68	204
	207 S3M		69	207
	210 S3M		70	210
	213 S3M	15 (150)	71	213
	216 S3M		72	216
	219 S3M		73	219
	225 S3M		75	225
	228 S3M		76	228
	231 S3M		77	231
	234 S3M	20 (200)	78	234
	237 S3M		79	237
	240 S3M		80	240
	243 S3M		81	243
	246 S3M		82	246
	252 S3M		84	252
同步齿形带	255 S3M	25 (250)	85	255
	258 S3M		86	258
	264 S3M		88	264
	267 S3M		89	267
	270 S3M		90	270
	276 S3M		92	276
	282 S3M	30 (300)	94	282