

丝杠支撑座

Support Units

方型·狭小间距
支持侧

NEW

新型号

绿色字体型号



狭小间距型



CAD 3D

型号	M 主体材质	S 主体表面处理
BTQ	S45C	四氧化三铁保护膜
BTQN		无电解镀镍
BTQB		低温镀黑铬

新型号



编号	名称	数量
1	轴承座	1
2	深沟球轴承	1
3	C型扣环	1

丝杠支撑座

型式		D ₁	A	B	C	E	H ₁	h	H	L	P	N	X	Y	Z	C型扣环	轴承型号
型号	No.																
BTQ (四氧化三铁 保护膜)	10	8	60	46	34	30	32.5	22	39	20	5.5	15	6.6	11	5	No. 8	608ZZ
	12	10			35			25	43			18			1.5	No.10	6000ZZ
	15	15	70	54	40	35	38	28	48	6.6	28	9	14	8.5	6.5	No.15	6002ZZ
	17	17	86	68	50	43	55	39	64							No.17	6203ZZ
	20	20	88	70	52	44	50	34	60	26	9	33	11	17.5	11	No.20	6004ZZ
	25	25	106	85	64	53	70	48	80	30						No.25	6205ZZ
	30	30	128	102	76	64	78	51	89	32	11	35	14	20	13	No.30	6206ZZ
	35	35	140	114	88	70	79	52	96							No.35	6207ZZ
BTQN (无电解镀镍)	40	40	160	130	100	80	90	60	110	37	14	37	18	26	17.5	No.40	6208ZZ
BTQB (低温镀黑铬)																	



订货范例
Order

型式

BTQ10





5 个工作日

狭小间距带缓冲型



CAD 3D

型号	M 主体材质	S 主体表面处理
BTQU	S45C	四氧化三铁保护膜
BTQUN		无电解镀镍



编号	名称	数量
1	轴承座	1
2	深沟球轴承	1
3	C型扣环	1
4	缓冲块	1

型式		D ₁	A	B	C	E	H ₁	h	H	L	P	N	X	Y	Z	C型扣环	缓冲块尺寸				轴承型号
型号	No.																a	b	t	e	
BTQU (四氧化三铁 保护膜)	10	8	60	46	34	30	32.5	22	39	20	5.5	15	6.6	11	5	No. 8	35	12	10	5	608ZZ
	12	10			35			25	43			18			1.5	No.10				6.5	6000ZZ
	15	15	70	54	40	35	38	28	48	6.6	28	9	14	8.5	6.5	No.15	44	16	14	11.5	6002ZZ
	17	17	86	68	50	43	55	39	64							No.17				15.5	6203ZZ
	20	20	88	70	52	44	50	34	60	26	9	33	11	18	11	No.20	67	18	14	16.5	6004ZZ
	25	25	106	85	64	53	70	48	80	30						No.25					6205ZZ



订货范例
Order

型式

BTQU10



5 个工作日